




concrete mixer bucket weighing



appsheet



WEIGHING AND RECIPES MANAGEMENT DEVICE INSTALLED ON BOARD

The Device is perfectly positioned in the cabin to give you the best view of its display and operability in choosing the recipe and its particular configuration. Its swivel mount allows you to direct the Device as you wish.



LOAD SENSORS TO DETERMINE THE LIFTING PRESSURE

The load sensors are inserted, by means of special fittings, into the hydraulic pipes that carry the oil to the lifting cylinders in order to measure the pressures involved during the variation of loads and movement.





SENSOR FOR WEIGHT DISPLAY



This sensor installed on the machine allows the display of the weight when the arm enters its intervention area during lifting.



specifications

		
power supply	9÷36Vdc	9÷36Vdc
working temperature	-40÷+80°C	-40÷+80°C
shocks	40G	40G
device/sensors protection	IP54/IP67	IP54/IP67
size	140x204x67	140x204x67
display	HD color	HD color
maximum capacity (kg)	6000	
measurement error	1%	2%
legal for trade		no

data management

		
production monitoring (products)	20	300
recipes/blending management	5	150
multi-tasking (simultaneous loads)	5	25
loadout full data management		large
job orders reception		yes
cloud connection	USB	USB-wireless
loading file download (.csv)	yes	yes

*see products datasheet for complete details